

# **SUMMARY**

- French context and electricity planning framework
- **Scenarios building**
- From market to network studies
- **Conclusions**



2



# **FRENCH STAKEHOLDERS**

# RTE work in transparency

	Regulator	Grid operator	Producers/ Suppliers	Public ministry of Energy
	CRE	RTE	EDF, ENGIE, Direct Energie, etc	DEGC
Missions	<ul> <li>Check the independence of the grid operator</li> <li>Check and approve network developments</li> <li>Check the fairness of electricity's market</li> </ul>	Ensure maintenance, development and operations of the network in total independence and transparence and at the minimum cost      Ensure security of supply	<ul> <li>Ensure profitability in liberalized electricity markets</li> </ul>	<ul> <li>Enforce political decisions in term of national energy decisions</li> </ul>
Power	<ul> <li>Can modify ten-year network development plan</li> <li>Can take coercive actions against stakeholders</li> </ul>		<ul> <li>Produce energy, build power plants and new services</li> <li>Supply final consumers at the best cost</li> </ul>	■ Law, decrees



### **RTE'S WORKFLOW: MULTI STAGE STUDIES**

## From market to network modeling

French ten-year National Generation Coherent and local Zonal studies network Adequacy Report assumptions corpus development plan · Build national coherent and distinct sets of assumptions · Break the national load · Identify network issues Test possible futures Identify network issues and generation to the thinness scale **Objectives** to the electrical zone electrical systems assumptions to the local Propose a development scale scale (below the region) plan Take into account other European countries · Assess shortfall risks


















#### **GENERATION SCENARIOS: HAZARDS VS UNCERTAINTIES**


### Two different unknowns


#### Hazards

- Unplanned outages
- Load forecast errors
- Wind and solar production
- Hydraulic storage levels
- ..

#### **Uncertainties**

- Economic growth
- Technologies
- Interconnexion developments
- New actors
- Commodities prices
- Political orientations
- Demography
- •







# **LONG-TERM SCENARIO BUILDING**

# Scenarios must framing the future


	Scenario		
	Generation	Load	
What	· 4 scenarios	4 scenarios     Distinct by the level of consumption more than the structure	
Why	Investment decision time range of producers     Lot of uncertainties (political, economic, regulations,)     Possible technological impact     Impossibility to forecast at this time range	Load level depending of uncertain economic growth Change in the use of electricity (electric cars,) etc Impossibility to forecast at this time range	
How	• Building of coherent scenarios framing the future • Need to be distinct to improve further sensitivity analyses  C D		






### **ZONAL APPROACH**

# Addition of an equivalent grid to the market model





Splitting national assumptions by zone (hourly step)

Model an equivalent network (Kirchhoff laws) at the scale of the zones

Identify zone with issues to optimize network studies (representative snapshot)

#### Each area is defined by assumptions on...

Its electrical demand and ancillary services (reserve) needs



Its generation fleet with its technical and economic characteristics













(most input data is yearly time series with a resolution of 1 hour)




#### PROBABILISTIC APPROACH


The best way to deal with hazards



#### **Key outputs:**

- Flow on the interconnexion
- Starting plan on each unit connected to the French
- Identification of constrained areas





#### **DC OPF SIMULATION**

# Accurate assessment of the congestions and their costs

For each constrained areas, detailed studies are conducted


They use a **DC Optimal Power Flow "OPF"** (i.e. Power flow only with active power), at an hourly step

These studies use a **full representation of the grid** and take in inputs :

- The previous Antares outputs
- The cost of generation per unit
- The cost of Co2 emission and the Co2 emission rate/unit

#### They allow to:

- Identify congestion on the grid
- Test different network topology: N, N-1
- Solve congestion at the best prices with redispatching
- Assess the price of congestion through redispatching



Prod. 120MW Down cost: 0€/MW Up cost: NA (PV gen.) CO2/MWh: 0t

CO2/1010111.00 CO2 cost: 25€ Prod. 60MW

Down cost: -40€/MW

Up cost: +55€/MWh


CO2/MWh: 0,49t

CO2 cost: 25€

Redispatching cost = 1345€/hour







# **FRENCH TYNDP IN ONE GLANCE**

# 4 key aspects

	Key aspects	How	
	Sensitivity to several scenario	Building several possible coherent futures     Test the results to several scenarios to check stability	
oO	Technical justification	Network studies     Identification of main factors (network congestion, lack of power,)	
•	Economic justification	Economic studies     Build relevant indicators (CBA, Social Welfare, etc)	
	Transparency and validation	Public debates on national assumptions Internal validation process Regulator approves the ten-year network development plan Public diffusion of reports	





#### **GENERAL WORKFLOW**

